

TO: All Nebraska PSAPs

FROM: Nebraska Public Service Commission

RE: County to County GIS Cooperative Agreement Template

DATE:

The migration in Nebraska from the existing, legacy 911 system to Next Generation 911 (NG911) requires cooperative geographic information systems (GIS) data development within and between PSAPs in the state. GIS data will be used to validate location information and route 911 calls in the NG911 environment. As such, seamless GIS data, developed and maintained to NG911 standards must exist within each public safety answering point (PSAP) in Nebraska. This same data also must be coordinated with neighboring counties in Nebraska as well as in bordering states.

The Nebraska Public Service Commission (PSC) is responsible for overseeing the Statewide 911 Program, including management of the 911 Emergency Services Internet Protocol (IP) Network (ESInet). To ensure cooperative GIS data development resulting in seamless GIS data to support the next generation core services (NGCS), the PSC is providing this cooperative agreement template for use by each PSAP to solidify the agreements for coordination across jurisdictional boundaries.

GIS Cooperative Agreement

Between:

Seward County 911

and

Saline County Sheriff's Office

Effective Date: February 12, 2021

Version Date Description

1.0 xxxxxxxx GIS Cooperative Agreement

1. Agreement Overview

This document represents a cooperative agreement between Seward County 911 and Saline County Sheriff's Office for defining and formalizing standard operating procedures (SOPs) and individual data development roles under the GIS data-preparation model.

This agreement outlines all established responsibilities regarding the NG911 implementation effort between the two parties. This agreement remains valid until superseded by a revised agreement mutually agreed to by both parties.

The purpose of this agreement is to establish the proper procedures necessary to ensure cooperative GIS data development for use in the NGCS for call routing (emergency call routing function, or ECRF) and address validation (location validation function, or LVF). Both parties enter into this agreement to define the roles each will fulfill in the development and maintenance of GIS data in support of NG911.

2. GIS Cooperative Agreement

The following detailed parameters are the responsibility each PSAP in the ongoing support of this agreement.

As NG911 service in Nebraska evolves, additional requirements for GIS data stewards will become necessary. This document specifically outlines the roles and responsibilities of each PSAP in maintaining GIS data across jurisdictional boundaries.

Routing both calls to the appropriate public safety answering point (PSAP) and emergency responders to the proper location continue to depend on the availability of highly accurate, fully attributed, and continually updated GIS data. PSAPs should work collaboratively with each other and with the PSC to realize seamless integration across borders between neighboring jurisdictions statewide and across state lines.

Data from local stakeholders will be used to construct and maintain the ECRF, LVF and location database (LDB), and to address the computer aided dispatch (CAD)-related mapping needs of Nebraska's PSAPs. For GIS data to be implemented in these components, GIS data must be seamless across jurisdictional boundaries. The gaps and overlaps in polygon features representing the PSAP, emergency service zones (ESZs), and provisioning boundaries must be eliminated. Road centerlines must be broken at intersections with these polygon features and snap to the endpoints of the road centerline features of neighboring PSAPs. Finally, the address attributes for road centerlines and address points must exist, be fully populated, and not overlap with attribution from other jurisdictions.

Included with this agreement:

- PSAPs identified on the signature page of this cooperative agreement will maintain dedicated GIS staff or a contracted GIS vendor to develop and maintain the GIS data necessary for NG911
 - All updates to GIS data shall be coordinated with affected neighboring jurisdictions to ensure against data overlap or gaps in line and polygon data.
 - PSAP, ESZ, and provisioning boundaries shall be reviewed, cooperatively by both PSAPs, on an annual basis
 - Boundary data maintenance shall follow the procedures outlined in the Nebraska NG911 GIS Boundary Resolution Workflow
 - Both PSAPs shall notify the PSC of data updates
- · All data, once validated, shall be provided to the PSC by both PSAPs
- Each PSAP agrees to identify and include in the broader PSAP plan a local GIS data authority for each PSAP

Where GIS services are provided under contract by a vendor, contracts should contain language supporting this agreement.

3. Service Scope

Pursuant to the deliverable regarding collaborative data development and maintenance, both PSAPs agree to:

- · Aggregate GIS data from all sources within the PSAP operating area
- Coordinate data updates with neighboring PSAPs prior to attempting to upload new data into the ESInet
- Work with neighboring PSAPs to resolve, in the interest of reduced call transfers, the PSAP boundary
- Notify all neighboring PSAPs and the PSC of upcoming or proposed changes to the PSAP boundary
- Validate, through the PSC, all changes to the GIS boundary datasets prior to submission to the ESInet to warrant against introducing errors and delaying further data updates

4. Merger Clause

This cooperative agreement shall remain in effect in the event of consolidation and/or division of PSAPs.

5. Periodic Review

This agreement is valid from the effective date outlined herein and is valid until further notice. This agreement should be reviewed annually at a minimum; however, in lieu of a review during any period specified, the current agreement will remain in effect.

The undersigned parties agree to adhere to the terms of this Cooperative Agreement.
PSAP Name: Saline County Sheriff's office
PSAP Representative: John Baumann
Signature:
Date: 2/3/202/
PSAP Name: SEWARD COUNTY 911 COMMUNICATIONS
PSAP Representative: ANDEW MATNEY
Signature:

Signatures

Date:

12 FEB 2021

Glossary of Terms

cronym	lein)	Demitor
ALI	Automatic Location Identification	Tabular reference for the current 911 system. Defines destination PSAP for every landline telephone number and cellular tower
ANI	Automatic Number Identification	Telephone number (TN) associated with the access line from which a call originates
BCF	Border Control Function	Provides a secure entry into the ESInet for emergency calls presented to the network
CAD	Computer-Aided Dispatch	A computer-based system that aids PSAP telecommunicators by automating selected dispatching and record-keeping activities
CLDXF	Civic Layer Data eXchange Format	A set of data elements that describe detailed street address information. All components are spelled out – no abbreviations
DHCP	Dynamic Host Configuration Protocol	A widely used configuration protocol that allows a host to acquire configuration information from a visited network and, in particular, an IP address
DNS	Domain Name System	A globally distributed database for the resolution of host names to numeric IP addresses
ECRF	Emergency Call Routing Function	A functional element in an ESInet; the ECRF is a Location to Service Translatio (LoST) protocol server where location information (either civic address or geo coordinates) and a Service Uniform Resource Name (Service URN) serve as input to a mapping function that returns a Uniform Resource Identifier (URI) used to route an emergency call toward the appropriate PSAP for the caller's location or toward a responder agency
ESInet	Emergency Services IP Network	Managed IP network that is used for emergency services communications, are which can be shared by all public safety agencies. It provides the IP transport infrastructure upon which independent application platforms and core service can be deployed, including, but not restricted to, those necessary for providing NG911 services
ESN	Emergency Service Number	A 3- to 5-digit number that represents one or more ESZs
ESRP	Emergency Service Routing Proxy	An i3¹ functional element that is a SIP proxy server; that the ESRP selects the next-hop routing within the ESInet based on location and policy. There is an ESRP on the edge of the ESInet. There is usually an ESRP at the entrance to a NG911 PSAP. There may be one or more intermediate ESRPs between them. Originating ESRP: The first routing element within the NGCS. It receives calls from the BCF at the edge of the ESInet. Terminating ESRP: The last ESRP for call in NGCS

¹ https://cdn.ymaws.com/www.nena.org/resource/resmgr/standards/NENA STA 010.2 i3 Architectu.pdf

teronym	Term	Definition		
ESZ	Zone	A geographical area that represents a unique combination of emergency service agencies (e.g., law enforcement, fire/rescue and emergency medical service) that is within a specified 911 governing authority's jurisdiction		
EIL	Extract, Transform, Load	Three database functions that are combined into one tool to pull data out of one database, properly map the fields to the schema of a second database, and place it into the other database		
GIO	Geographic Information Office	The State level division of DoIT tasked with supporting existing and future efforts to improve the quality of GIS in Maryland through coordination and collaboration with the larger GIS community		
GIS	Geographic Information System	A system for capturing, storing, displaying, analyzing and managing data and associated attributes which are spatially referenced		
i3 PSAP	NENA i3 introduces the concept of an ESInet, which is designed as an IP-based internetwork (network of networks) shared by all agencies that may be involved in any emergency. A PSAP that is capable of receiving IP-based signaling for delivery of emergency calls and for originating calls and is conformant to NENA-STA-010 and other specifications for such PSAPs			
ΙP	Internet Protocol	The method by which data is sent from one computer to another on the ESInet Internet or other networks		
LDB	Location Database	The server that retains all of the current information, functionality, and interfaces of today's ALI and can utilize the new protocols required in an NG911deployment		
LIS	Location Information Server	A functional element in an IP-capable originating network that provides locations of endpoints (i.e., calling device)		
LVF	Location Validation Function	A functional element in an NGCS that is a LoST protocol server where civic location information is validated against the authoritative GIS database information		
MSAG	Master Street Address Guide	Tabular reference for address validation in the current 911 system. Defines all possible addresses within a jurisdiction		
NENA	National Emergency Number Association	Standards body for 911 and NG911		
NG911	Next Generation 911	NG911 refers to an initiative aimed at updating the 911 service infrastructure is the United States and Canada to improve public emergency communications services in a growingly wireless mobile society		
NGCS	Next Generation Core Services	The base set of services needed to process a 911 call on an ESInet. Includes the ESRP, ECRF, LVF, BCF, Bridge, Policy Store, Logging Services and typical IP services such as DNS and DHCP. The term NGCS includes the services and not the network on which they operate.		
PRF	Policy Routing Function	That functional component of an Emergency Services Routing Proxy that determines the next hop in the SIP signaling path using a policy		

40.00	Jem	C Melinition **
PSAP	Public Safety Answering Point	The entity responsible for receiving 911 calls and processing those calls according to a specific operational policy
PSC	Public Service Commission	Nebraska state agency responsible for regulating 911
SI	Spatial Interface	A standardized interface between the GIS and the functional elements that consume GIS data, such as the ECRF and/or LVF
SIP	Session Initiation Protocol	A protocol specified by the Internet Engineering Task Force (IETF) (RFC3261) that defines a method for establishing multimedia sessions over the internet. Used as the call-signaling protocol in VoIP, NENA i2 and NENA i3
SOP	Standard Operating Procedure	A written directive that provides a guideline for carrying out an activity.
TFOPA	Task Force on Optimal Public Safety Answering Point Architecture	The Federal Task Force directed to study and report findings and recommendations on structure and architecture in order to determine whether additional consolidation of PSAP infrastructure and architecture improvements would promote greater efficiency of operations, safety of life, and cost containment while retaining needed integration with local first responder dispatch and support
VolP	Voice Over Internet Protocol	Telephone service provided through the internet rather than traditional telephone lines. This includes FIO5™, cable service such as Comcast and Time Warner, and purchased devices like Ooma, Google Voice, or Magic Jack

WENDY L. ELSTON COUNTY ATTORNEY

BARBARA J. ARMSTEAD



LORY A. PASOLD
CHIEF DEPUTY

ASHLEY A. DORWART

SEWARD COUNTY ATTORNEY

261 S. 8th Street #211 SEWARD, NEBRASKA 68434

> PHONE (402) 643-2795 FAX (402) 643-4614

Request for County Attorney Review

** Please allow at least 1 week for review **

Name Andrew Matney

Contact phone number or email:

Department E-911

Date

Brief Description of subject of the document County to County GIS Cooperative Agreement

To be placed on County Board agenda?

If yes, meeting date requested

Notes GIS/Mapping Agreement between Saline County & Seward Co 911

To be completed by the Seward County Attorney's office:

Approved 🗸

Ready for board agenda

Follow up needed

Other Changes per email exchanges with Saline County made; effective date and names of parties to the agreement added.

Reviewed by:

Please bring completed form with supporting documents to the County Attorney's office, or email to BArmstead@co.seward.ne.us. We will do our best to be in contact with you as soon as possible.